

Investigation of the Impacts of Solid Waste Disposal Sites on Groundwater in Nasarawa Metropolis, Nigeria

MUHAMMAD SANI ALIYU¹, JIBRIN ABDULLAHI MAIRIGA², USMAN HASSAN AHMED³,
SALEH U. BORORI⁴, ABUBAKAR HARUNA⁵

^{1, 3, 5} Department of Civil Engineering Technology, Federal Polytechnic Nasarawa, Nigeria

² Department of Building Technology, Federal Polytechnic Nasarawa, Nigeria

⁴ Department of Science and Laboratory Technology, Federal Polytechnic Nasarawa, Nigeria

Abstract- Population increase generates concerns for waste disposal. Absence of standard sanitary-disposal methods has left many city residents with open dumpsites as their only means of disposing waste, thereby resulting in leachate from the decomposition of these waste materials, which will later pollute underground water. The research investigated the effects of solid waste disposal sites on underground water quality through the examination of some physical and chemical properties of water in hand-dug wells around some selected disposal sites in Nasarawa metropolis, Nasarawa State. Three hand-dug wells were sampled at various distances from each dumpsite. The samples were thoroughly tested at the Federal Ministry of water resource, Regional Water Quality Laboratory, Minna, Niger state. The overall quality of the water was determined using the Water Quality Index method. The results showed high degree of non-conformity with W.H.O and NSDWQ standards. The study of chemical properties from the three wells showed that seven (7) parameters (dissolved oxygen, total dissolved solids, total suspended solids, conductivity, chloride, total hardness, manganese) are above W.H.O. limits in some samples. Also the Water Quality Index of the three samples; Unguwar Bai1, Unguwar Bai2 and Student Village which had been calculated to be 1072.2, 1867.1 and 69.85 respectively, were far out of the range of safe drinking water quality (according to Weighted Arithmetic Water Quality Index Rating). The water is therefore not safe for human consumption and there is a serious need to improve its quality. Therefore the need for adequate planning, design and construction vis-a-vis strategic management of waste becomes very crucial.

Indexed Terms- Solid Waste, Disposal Sites, Water Quality Index, Groundwater

I. INTRODUCTION

The intensity of man's activities has led to increased volume of solid waste worldwide despite the current level of technological advancement and industrialization. Explosive population growth is one other major factor responsible for increased municipal solid waste (MSW). Land filling of municipal solid waste is a common waste management practice and one of the cheapest methods for organized waste management in many parts of the world (El-fadel M. Lekie J.O. 1997). The study therefore focusses on the reckless abundance of solid wastes (evident by the number of open dumpsites) within Nasarawa Metropolis and the impacts of these wastes on neighbouring groundwater sources. A thorough analysis of certain water parameters would assist in revealing the impacts of solid wastes on the groundwater. In most parts of Nasarawa Metropolis refuse are dumped indiscriminately on open grounds, without considering the direct and indirect health threats associated therewith. Just like what obtains here (Nasarawa Metropolis), Landfill operations are most feasible in developing countries as land is vastly available and moderately inexpensive. Even in many developed countries where land is scarce and where policies of reduction, reuse and diversion from landfills are strongly promoted, great percentage of their generated MSW are still land filled. For instance, in 2006, out of the 251 million tons of MSW generated in the United States of America, 138.2 million tons representing 55% was disposed of in landfills (USEPA, 2007). In England, out of the

29.1million tons of municipal solid waste generated between 2003 and 2004, 72% was land filled (DEFRA, 2005). Landfills may however pose serious threat to the quality of the environment if incorrectly secured and improperly operated. The threat to surface and ground waters could be deleterious. The scale of this threat depends on the composition and quantity of leachate and the distance of a landfill from water sources (Somczyska B. Somczyska T. 2004) .This study was undertaken to assess the impact of solid waste disposal sites on groundwater in Nasarawa metropolis, Nasarawa State.

II. MATERIALS AND METHOD

2.1 Description of Study Area

The study areas are in Nasarawa metropolis of Nasarawa state and are located between Coordinates: 8°32'N8°18'E. Nasarawaas a Local Government Area in Nasarawa State, Nigeria. It has an area of 5,704 km² and a population of 189,835 according to the 2006 census.



Location of Nasarawa State in Nigeria

FIGURE 3.1: Map Sketch of Nigeria Showing the Location of Nasarawa State.

2.2 Groundwater Collection Procedure

Samples for groundwater were taken from points identified as Unguwar Bai 1, Unguwar Bai2 and Student Village. Sample from Unguwar Bai 1 (for contaminated groundwater sample) was a well located about 5m downstream of the dumpsite. The well was suspected to be contaminated with leachate from the dumpsite on account of its spatial and hydrologic characteristics such as proximity to the

dumpsite, groundwater flow direction and topography. Unguwar Bai 2 (for contaminated groundwater sample) was a well about 10m downstream of the dumpsite. This well was suspected to be contaminated by leachate from the dumpsite due to its downstream location with respect to hydrologic and spatial influences. Sample from Student Village was a well located about 13m, downstream a dumpsite that had been cleared. All samples were obtained on same day and were collected in previously sterilized containers and stored in iced boxes at 4°C and conveyed to the laboratory for analysis within 5 to 8 hours.

Water samples were measured and analysed for temperature (°c), turbidity (NTU), conductivity, Dissolved Oxygen (DO), Total Dissolved Solids (TDS), total suspended solids (TSS),chloride (Cl), Calcium, Total Hardness, iron (Fe), Copper (Cu), Nitrate, Zinc, manganese (Mn), Chromium (Cr6+), lead (Pb), Silicate, Chemical Oxygen Demand (COD), total coliform (TC), colour; and Taste. Analysis of groundwater for the above listed parameters was done in accordance with standard methods for the analysis of water and wastewater (APHA, 1992).

2.3 Determination of physico-chemical parameters

Physical and chemical parameters were determined in each water sample according to Standard methods as recommended by relevant authorities such as World Health Organization (WHO), United State Environmental Protection Agency (US- EPA).

2.3.1 Determination of Temperature.

The temperature was determined in the sample with an Hg filled glass thermometer. The thermometer was dipped into each sample and observed for movement of the mercury (Hg) thread, reading was taken at point when there no more development. It was ensured that the thermometer was brought to room temperature (30°C) before each reading was taken and held upright to avoid parallax error (US- EPA, 1983; APHA-AWWA-WPCF, 1985; Trivedy and Goel, 1986).

2.3.2 Determination of pH

The pH meter was standardized using buffer solutions of pH 4 and 9, the response of the pH meter

corresponded with the manual temperature of the buffer solution at both instances. Before each sample was measured, the electrode was placed in distilled water. In measuring the pH of sample, the meter was placed inside the sample and the electrode response taken. This was repeated thrice for accuracy for all samples measured (US-EPA, 1983; APHA-AWWA-WPCF, 1985; Trivedy and Goel, 1986).

2.3.3 Determination of Conductivity

A conductivity meter was used. The conductivity cell was calibrated with the standard KCl solution. The sample was brought to room temperature. The conductivity cell was washed with portion of the sample and then filled completely with the sample ensuring there was no air bubble adhered to the electrode and reading taken. The results were expressed as micro Siemens per centimetre ($\mu\text{S}/\text{cm}$) (US – EPA, 1983; APHA – AWWA – WPCF, 1985; Trivedy and Goel, 1986; NWRI, 2001).

2.3.5 Determination of turbidity

- Apparatus: Turbidity Meter
- Procedure: Switch on the Turbidity Meter by pressing the ON/OFF key [...RD...] and insert cleaned prepared calibration standards Cal 800NTU and press read. Remove the first one, insert the second one cal200NTU and press read. Remove the second one, insert the third one Cal 100NTU and press read. Fill the sample cell with the sample to the mark and insert it to the sample holder, Press READ/ENTER key, the display blinks [...Rd...] and a value will appear, which the turbidity value is. Repeat step for other samples (if any).

2.3.6 Determination of Total Hardness

The EDTA titration method was used in determining the total hardness of the samples. The sample was shaken thoroughly. 25cm^3 of the sample was taken and diluted with 50cm^3 of distilled water and transferred quantitatively into a clean 250cm^3 Erlenmeyer flask. 2cm^3 of buffer solution ($\text{NH}_4\text{CL} - \text{NH}_4\text{OH}$) was added, followed by two drops of Eriochrome Black indicator and the sample titrated with standard EDTA solution that has been standardized using the standard calcium solution. The formation of blue colour indicated the end point, titre value was recorded. (US-EPA, 1983; APHA-

AWWA-WPCF, 1985; Trivedy and Goel, 1986; NWRI, 2001)

- Calculation: Hardness (EDTA) as mg CaCO_3

$$= \frac{A * B * 100}{\text{ml of sample}}$$

Where; A = Titre for sample (ml) and; B = mg CaCO_3 equivalent to 1.00ml EDTA titrant.

2.3.7 Determination of Total Dissolved Solids

100ml of the sample was quantitatively transferred into an evaporating dish that has been previously weighed and dried in an oven for one hour and cooled in desiccators. The content of the dish was evaporated to dryness on a water-bath to a constant weight. The residue was dried in an oven between $103-105^\circ\text{C}$ for two hours, cooled in a desiccators and the difference in weight calculated (US-EPA, 1983; APHA-AWWA-WPCF, 1985; Trivedy and Goel, 1986; NWRI, 2001).

$$\text{Calculation TDS (mg/l)} = \frac{\text{mass of suspended solid} * 100}{\text{ml of sample}}$$

2.3.8 Determination of Chemical Oxygen Demand (COD)

20cm^3 of sample was placed in a 500cm^3 refluxing flask. 10cm^3 of standard $\text{K}_2\text{Cr}_2\text{O}_7$ with several glass beads already heated for 1 hour was added and 30cm^3 of sulphuric acid containing 0.4g of Ag_2SO_4 was added slowly and mixed to dissolve Ag_2SO_4 . It was then refluxed for 1hour. It was cooled and diluted with 150cm^3 of distilled water, the mixture was titrated against standard ferrous ammonium sulphate (FAS) using 0.15cm^3 ferrion indicator. Reflux of blank containing the reagents was also titrated as above. (Nsi, 2007).

$$\text{Calculation: COD as } \text{O}_2/\text{l} = \frac{(A-B)*M*8000}{\text{ml of sample}}$$

where; A = ml FAS used for blank,

B = ml FAS used for sample and

M = Molarity of FAS.

2.3.9 Determination of Chloride

Highly coloured samples was treated with $\text{Al}(\text{OH})_3$ suspension, allowed to settle and then filtered. 50ml of the sample was placed in 250cm^3 flask. 1.0cm^3 of K_2CrO_4 indicator solution was added and sample titrated with standard AgNO_3 (0.14M) to a reddish brown colour. Blank and standard titrations were

carried out. (US-EPA, 1983; APHA-AWWA-WPCF, 1985; Trivedy and Goel, 1986; NWRI, 2001; Nsi, 2007).

III. RESULT ANALYSES AND DISCUSSION

3.1 Physical Parameters

Analysis of the physical properties of sampled groundwater (Table 4.1) shows that temperature ranged between 28.8°C - 28.9°C, indicating the presence of foreign bodies such as active micro-organisms (Akinbile and Yusoff, 2011; Jaji et al., 2007). Algae was also observed growing in and around most of the well sampled. The complete data set is provided in Appendix D and E.

Table 4.1: Results of Physical Parameters Determination.

s/no	Parameters	Unguwar Bai 1	Unguwar Bai 2	Student Village
1	Ph	6.73	7.42	6.15
2	Temperature (°c)	28.90	28.9	28.8
3	Turbidity (NTU)	1.00	0.00	0.00

3.2 Chemical Parameters

The concentrations of chemical parameters, inclusive of heavy metals, of groundwater samples are shown in Tables 4.2 and 4.3 compared with WHO and NSDWQ standards

Table 4.2: concentration of chemical and heavy metal parameters in the tested samples.

s/no	Parameters	Unguwar Bai1	Unguwar Bai 2	Student Village
1	Dissolved oxygen (mg/l)	6.20	6.40	6.92
2	Total dissolved solid (mg/l)	1087	1379	318
3	Total suspended solid(mg/l)	5.00	0.00	6.00
4	Chloride (mg/l)	276.7	299.9	52.0
5	Conductivity (µs/cm)	1632	2060	478
6	Calcium (mg/l)	178.2	60.9	35.0
7	Total hardness (mg/l)	693	563	143
8	Iron (mg/l)	0.34	0.07	0.35
9	Copper (mg/l)	1.03	1.20	0.44
10	Nitrate (mg/l)	3.40	63.0	39.1
11	Zinc (mg/l)	2.33	2.55	0.69
12	Manganese (mg/l)	3.30	5.40	0.21
13	Chromium (mg/l)	0.09	0.13	0.03

14	Lead (mg/l)	0.02	0.05	0.00
15	Silicate (mg/l)	25.0	14.8	16.5
16	COD (mg/l)	0	0	0

Table 4.3: comparison between parameter concentrations, WHO standards and NSDWQ standards.

s/no	Parameters	Unguwar Bai 1	Unguwar Bai 2	Student Village	WHO	NSDWQ
1	Ph	6.73	7.42	6.15	6.5-8.5	6.8-8.5
2	Temperature (°c)	28.90	28.9	28.8	25	NS
3	Turbidity (NTU)	1.00	0.00	0.00	1-5	1-5
4	Dissolved oxygen (mg/l)	6.20	6.40	6.92	2.0	NS
5	Total dissolved solid (mg/l)	1087	1379	318	500	500
6	Total suspended solid(mg/l)	5.00	0.00	6.00	3.0	NS
7	Chloride (mg/l)	276.7	299.9	52.0	250	250
8	Conductivity (µs/cm)	1632	2060	478	1000	1000
9	Calcium (mg/l)	178.2	60.9	35.0	300	NS
10	Total hardness (mg/l)	693	563	143	100	150
11	Iron (mg/l)	0.34	0.07	0.35	0.3	0.3
12	Copper (mg/l)	1.03	1.20	0.44	2.0	1.0
13	Nitrate (mg/l)	3.40	63.0	39.1	10	50
14	Zinc (mg/l)	2.33	2.55	0.69	NS	3.0
15	Manganese (mg/l)	3.30	5.40	0.21	0.05	0.2
16	Chromium (mg/l)	0.09	0.13	0.03	0.05	0.05

3.2 Discussion of Result

The presented results above are analysed using the Weighted Arithmetic Water Quality Index (WQI) as discussed in the previous chapter.

The Weighted Arithmetic Water Quality Index allows for easy computation of the quality of water and its source by using a mathematical formula.

The results from this study clearly demonstrate that the water quality obtained from the sampled wells are unfit for human consumption. This is because the calculated Water Quality Index (for all samples) exceeded the normal range with unguwar bai and 2nd unguwar bai water samples having WQI values of 1072.2 and 1867.1 respectively and student village

sample 69.85 (Appendix A,B,C). The summary of the water quality index is presented in table 4.4 according to Weighted Arithmetic Water Quality Rating.

Table 4.4: quality rating of tested water-quality parameters

Water samples	WQI	Remarks
Unguwar bai 1	1072.2	Unsuitable for drinking purposes
Unguwar bai 2	1867.1	Unsuitable for drinking purposes

Student village	69.85	Poor water quality
-----------------	-------	--------------------

CONCLUSION

The study suggests (from analysis) indiscernible transformation of decomposed waste into leachate from the base of the landfill to be the point source of groundwater pollution. This obviously could limit groundwater functions for various purposes (such as domestic, industrial and agricultural). Different health related problems could also be attributed to groundwater pollution.

The dumpsites are neither properly managed to contain leachate nor are they operated in a way that keeps out rainwater, which is responsible for the formation and percolation of leachate. As a result, groundwater and soil around these areas are contaminated. Concentrations of electrical conductivity (EC) in Uguwar Bai 1 and Uguwar Bai 2 groundwater samples are as high as 1632 and 2060 μ s/cm respectively compared to the required limit of 1000 μ s/cm. Also, concentrations of total dissolved solid (TDS) in Uguwar Bai 1 and Uguwar Bai 2 are equally as high as 1087mg/l and 1379mg/l respectively compared to the maximum limit of 500mg/l. Hence samples from these two wells are profoundly contaminated by dissolved wastes, therefore, they pose serious health threats to the consumers. The research work has revealed that leachate is the main agent for pollution of groundwater sources in the study area (from the high concentration of TDS). As such, the location of the dumpsite close to the groundwater sources and especially, the fact that rainwater is allowed to flow through the waste, are important precursor conditions for the observed pollution. The results from the research also proved that the groundwater sources sampled are unfit for consumption due to their high degree of contamination as deemed from the overall water quality index.

Season have been found to influence the magnitude as well as the occurrence of pollution emanating from the dumpsites. Rainwater flows through the waste in the dumpsite, which is not covered, leaching out

pollutants, which later moves away from the dumpsite.

Conclusively, both surface and groundwater may be available in appreciable quantity in Nasarawa metropolis owing to its geographical location, but quality water sources are rare.

REFERENCES

- [1] Adedibu, A. A. (1985). A comparative analysis of solid waste composition and generation in cities of developing nations. *The Environmentalist*, 5(2), 123 – 128
- [2] Adewole, A. T. (2009). Waste management towards sustainable development in Nigeria: A case study of Lagos State. *International NGO Journal*, 4(4), 173-179
- [3] Afolayan, O. S., Ogundele, F. O., Omotayo, A. (2012). Comparative analysis of the effect of closed and operational landfills in groundwater quality in Solous, Lagos, Nigeria. *Journal of Applied Technology in Environmental Sanitation*, 2(1), 67-76.
- [4] Aghazadeh, N. & Mogaddam, A. A. (2010). Assessment of groundwater quality and its suitability for drinking and agricultural uses in the Oshnevieh Area, northwest of Iran. *Journal of Environmental Protection*, 1, 30-40.
- [5] Akinbile, O. C. & Yusoff, M. S. (2011). Assessment of groundwater quality near a municipal landfill in Akure, Nigeria. 2011 2nd International Conference on Environmental Science and Technology. Singapore: IACSIT Press
- [6] Balogun, M. R. & Longe E. O. (2008). Hydrological implication of solid waste disposal on groundwater quality in urbanized area of Lagos State, Nigeria. *International*
- [7] Bhatnagar, A. & Devi, P. (2012). Applications of correlation and regression analysis in assessing lentic water quality: a case study at Brahmsarovar Kurukshetra, India *International Journal of Environmental Sciences* 3(2)
- [8] Bhattacharya, K. A. (2010). Artificial groundwater recharge with a special reference

- to India. International journal of research and reviews in applied sciences, 4(2)
- [9] Bhide, A.D. and Sundersan, B.B. 1983 “Solid Waste Management in Developing Countries”, Indian National Scientific Documentation Centre, New Delhi, India, 1983.
- [10] Brodtkin. E., Copes, R., Mattman, A., Kennedy, J., Kling, R. & Yassi, A. (2007). Lead and mercury exposures: interpretation and action. Canadian Medical Association Journal, 176(1), 59
- [11] Bulut, Y. & Baysal, Z. (2006). Removal of Pb (II) from wastewater using wheat bran. Journal of Environmental Management 78(2), 107-113
- [12] Burman, P. (2009). Trash or Treasure. [Retrieved December 27, 2013, from <http://www.carbonfund.org/blog/item/4430-trash-treasure>]
- [13] Dhamija, S. K. & Jain, Y. (1995). Studies on the water quality index of a lentic water body at Jabalpur MP. Pollution Research, 14(3), 141.
- [14] Dockery, D. W, Cunningham, J., Damokosh, A. L., Neas, L. M., Spengler, J. D., Koutrakis, P., Ware, J. H., Raizenne, M. & Speizer, F. E. (1996). Health Effects of Acid Aerosols on North American Children: Respiratory Symptoms. Environmental Health Perspectives, 104(5)
- [15] Donalson, W. E. (1980). Trace element toxicity, In: Introduction to Biochemical Toxicology. New York: Elsevier, 330 - 340.
- [16] El-Fadel, M., Findikakis, A. N. & Leckie, J. O. (1997). Environmental impacts of solid waste landfilling. Journal of Environmental Management, 50(1), 1-25
- [17] Elliott, S. J. & Taylor, S. M. (1996). Worrying about waste: Diagnosis and prescription. In: Munton, D. (ed.) Siting by Choice: Waste Facilities, NIMBY and Volunteer Communities (pp 290-318). Washington DC: Georgetown University Press.
- [18] Eludoyin, A. O. & Oyeku, O. T. (2010). Heavy metal contamination of groundwater resources in a Nigerian urban settlement. African Journal of Environmental Science
- [19] Fatta, D., Papadopoulos, A. & Loizidou, M. (1999). A Study on the landfill leachate and its impact on the groundwater quality of the Greater Area. Environmental Geochemistry and Health, 21: 175-190
- [20] Gleick, P. H. (1996). Water resources. In Encyclopedia of Climate and Weather, ed. by S. H. Schneider, Oxford University Press, New York, vol. 2, pp.817-823.
- [21] Harter, T. (2003). Groundwater quality and groundwater pollution. [Retrieved December 27, 2013, from <http://anrcatalog.ucdavis.edu/pdf/8083.pdf>]
- [22] Horton, R. K. (1965). An index number system for rating water quality. Journal of Water Pollution, 37(3), 300-305
- [23] Jackson, S. (1985). Anatomy & Physiology for Nurses. Nurses' Aids Series (9th edition.). London: Bailliere Tindall
- [24] Jarvie, H. P., Whitton, B. A. & Neal, C. (1998). Nitrogen and phosphorus in east coast British rivers: speciation, sources and biological significance. Science of the Total Environment, 210211:79-109
- [25] Jeje, L. K. (1983). Aspects of Geomorphology in Nigeria. In: Geography of Nigeria (pp 17-44). Nigeria: Heinemann Educational
- [26] Koertel, A. & Spillman, P. (2005). The Teheran Model – The large scale introduction of a static composting process for high water content municipal waste in arid regions
- [27] Kola-Ogunsanya, A. (2012). Impact of Municipal Solid Wastes on Underground Water Sources in Nigeria. European Scientific Journal 8(11), 2
- [28] Kostova, I. (2006). Leachate from sanitary landfills - origin, characteristic treatment. University of Architecture, Civil Engineering and Geodesy, “Iskar’s Summer School”- Borovetz, 26-29 July
- [29] Lee, G. F. & Jones-Lee, A. (1993b). Groundwater pollution by municipal landfills: Leachate composition, detection and water quality significance. International Waste Management and Landfill Symposium, 1093-1103

- [30] Lee, S. & Kitanidis, P. K. (1993). Analysis of groundwater flow and travel time for a landfill site in an arid region with a thick vadose zone. *Hydrological Processes*, 7, 373-387
- [31] Lenntech (2012). Water treatment solutions [Retrieved December 20, 2013 from http://www.lenntech.com/why_the_oxygen_dissolved_is_important.htm]
- [32] Leton, T. G. & Omotosho, O. (2004). Landfill operations in the Niger delta region of Nigeria. *Engineering Geology*, 73(1-2), 171-177
- [33] Lewis, R. J. (1991). Hazardous chemicals desk reference (2nd eds), Reinhold: Van Nostrand Liao, S. W., Gau, H. S., Lai, W. L., Chen, J. J. & Lee, C. G. (2007). Identification of pollution of Tapeng Lagoon from neighbouring rivers using multivariate statistical method. *Journal of Environmental Management*, 88(2), 286-292
- [34] Maddock, B.G. Taylor, D. (1977). The acute toxicity and bioaccumulation of some lead compounds in marine animals. In: Lead in the marine environment. Proceeding of the international experts discussion on lead occurrence, Fate and pollution in the marine environment, Rovinj, Yugoslavia, 18 - 22 October, 233 – 261
- [35] Mahvi A. H., Nouri, J., Babaei, A. A. & Nabizadeh R. (2005). Agricultural activities impact on groundwater nitrate pollution. *International Journal of Environmental Science and Technology* 2(1):41-47
- [36] Modak P R and Nangare P B. 2011, "Quantitative and Qualitative Assessment of Municipal Solid Waste for Nagpur City", *J.Env.Res. & Sc.*, Vol.2, Issue 2, April-June, 2011, pp. 55-61.
- [37] Mor, S., Ravindra, K., Dahiya, R. P. & Chandra, A. (2006). Leachate Characterization and Assessment of Groundwater Pollution near Municipal Solid Waste Landfill Site. *Environmental Monitoring and Assessment*, 118: 435 – 456
- [38] Mull, E. J. (2005). Approaches toward Sustainable Urban Solid Waste Management: Sahakaranagar Layout. Thesis (M.Sc) - Lund University
- [39] Nigerian Industrial Standard (2007). Nigerian Standard for Drinking Water Quality (NSDWQ), ICS
- [40] Northeast Georgia Regional Development Center (2000). Watershed Protection Plan Development Guidebook. [Retrieved October 14, 2014 from https://epd.georgia.gov/sites/epd.georgia.gov/files/related_files/site_page/devwtrplan_b.pdf]
- [41] Nouri, J., Karbassi, A. R. & Mirkia, S. (2008). Environmental management of coastal regions in the Caspian Sea. *International Journal of Environmental Science and Technology* 5(1):43-52
- [42] Odumosu, T. (1999). In: Balogun, Y. & Ojo, K. Lagos State in Maps (pp 1-5). Ibadan: Rex Charles
- [43] Ogundiran, O.O. & Afolabi, T. A. (2008). Assessment of the physicochemical parameters and heavy metals toxicity of leachates from municipal solid waste open dumpsite. *International Journal of Environmental Science and Technology*, 5(2), 243-250
- [44] data. Seventh International Waste Management and Landfill Symposium, vol. IV, (eds. T.H. Christensen, R. Cossu, and R. Stegmann) (pp. 117-124) Cagliari: CISA
- [45] Rowe, R. K., Quigley, R. M. & Booker, J. R (1995). *Clayey Barrier Systems for Waste Disposal Facilities*. London: E & FN Spon (Chapman & Hall)
- [46] R.M, McCleiland, N.J., Deiniger, R.A. and O'Connor, M.F.A. "Water quality index – crossing the physical barrier", (Jenkis, S.H. ed.) *Proceedings in International Conference on water pollution Research Jerusalem* 6. 787-797. 1972.
- [47] Singha, S. K. (1995). Probability of rural ponds water at Muzaffarpur (Bihar) a note on water quality index. *Pollution Research*, 14(1), 135-140
- [48] Slomczynska, B. & Slomczynski T. (2004). Physicochemical and toxicological characteristics of leachates from MSW landfills. *Polish Journal of Environmental Studies*, 13(6), 627-637.

- [49] Tiwari, T. N. & Mishra, M. A. (1985). A preliminary assignment of water quality index of major Indian rivers. *Indian Journal of Environmental Protection*, 5:276-279.
- [50] Toivonen, J. & Österholm, P. (2010). Identifying the impact of acid sulfate soils on a humic boreal Lake. 2010 19th World Congress of Soil Science, Soil Solutions for a Changing World
- [51] Twaddle, A. C. (1996). Health system reforms - Toward a framework for international comparisons. *Social Science & Medicine* 43(5), 637-654
- [52] U.S. Environmental Protection Agency (2001). Parameters of water quality – Interpretations and Standards. [Retrieved October 15, 2014 from https://www.epa.ie/pubs/advice/water/quality/Water_Quality.pdf]
- [53] U. S. Environmental Protection Agency (2013). National Primary Drinking Water Regulations [Retrieved October 14, 2014 from <http://water.epa.gov/drink/contaminants/index.cfm>]
- [54] World Health Organization (2006). Rapid Assessment of Drinking Water Quality. Country Report Nigeria
- [55] World Health Organization, (2004). Guidelines for Drinking Water Quality (3rd ed.) Vol.1 Recommendation, Geneva, 515
- [56] Yeh, M.S., Shaun, H. Y., Chang, L. C, Lin, Y. P. (2008). Establishing index wells for monitoring groundwater quality using multivariate geostatistics. *Journal of the Chinese Institute of Civil and Hydraulic Engineering*. 20(3), 315-330
- [57] Yogedra, K. & Puttaiah, E.T. (2008). Determination of water quality index and suitability of an urban waterbody in Shimga town. In: Sengupta, M. K. & Dalwani, R. (Eds.).*Proceedings of Taal 2007: The World Lake Conference*.342-346.
- [58] Zevenhoven, R. & Kilpinen, P. (2001). Control of Pollutants in Flue Gases and Fuel Gases.

APPENDIX

Appendix A: water quality index table for student village sample.

Parameter	v_i	v_o	s_i	$\frac{1}{s_i}$	$Q_{i=100} \frac{v_i - v_o}{s_i - v_o}$	$W_{i=\frac{k}{s_i}}$	$Q_i W_i$
pH	6.15	7	8.5	0.12	-56.67	0.00081	-0.046
Turbidity	0	0	5	0.2	0	0.0014	0
E.C	478	0	1000	0.001	47.8	0.0000069	0.00033
DO	6.92	14.6	5	0.2	80	0.0014	0.112
TDS	318	0	500	0.002	63.6	0.000014	0.00089
TSS	6	0	3	0.33	200	0.0023	0.46
Chloride	52	0	250	0.0004	20.8	0.000028	0.00058
Calcium	35	0	300	0.0033	11.67	0.000023	0.00027
T. hardness	143	0	150	0.0067	95.33	0.000046	0.0044
Iron	0.35	0	0.3	3.33	116.67	0.023	2.68
Copper	0.44	0	2	0.5	22	0.0035	0.077
Nitrate	39.1	0	10	0.1	391	0.00069	0.27
Zinc	0.69	0	1	1	69	0.0069	0.48
Manganese	0.21	0	0.05	20	420	0.138	57.96
Chromium	0.03	0	0.05	20	60	0.138	8.28
Lead	0	0	0.01	100	0	0.69	0
\sum total				145.79		1.0061	70.28

$$K = \frac{1}{\sum \frac{1}{s_i}} = \frac{1}{145.79} = 0.0069$$

$$WQI = \frac{\sum(Q_i W_i)}{\sum W_i} = \frac{70.28}{1.0061} = 69.85$$

Appendix B: water quality index table for unguwar bai sample.

parameter	v _i	v _o	s _i	$\frac{1}{s_i}$	$Q_i = 100 \left(\frac{v_i - v_o}{s_i - v_o} \right)$	$W_i = \frac{k}{s_i}$	Q _i W _i
pH	6.73	7	8.5	0.12	-18	0.00082	-0.015
Turbidity	1	0	5	0.2	20	0.0014	0.028
E.C	1632	0	1000	0.001	163.2	0.0000069	0.00113
DO	6.2	14.6	5	0.2	87.5	0.0014	0.12
TDS	1087	0	500	0.002	217.4	0.000014	0.003
TSS	5	0	3	0.33	166.67	0.0023	0.38
Chloride	276.7	0	250	0.004	110.68	0.000028	0.003
Calcium	178.2	0	300	0.0033	59.4	0.000023	0.0014
T. hardness	693	0	150	0.0067	462	0.000046	0.02
Iron	0.34	0	0.3	3.33	113.33	0.023	2.61
Copper	1.03	0	2	0.5	51.5	0.0035	0.18
Nitrate	3.40	0	10	0.1	34	0.00069	0.02
Zinc	2.33	0	1	1	233	0.0069	1.61
Manganese	3.3	0	0.05	20	6600	0.138	910.8
Chromium	0.09	0	0.05	20	180	0.138	24.84
Lead	0.02	0	0.01	100	200	0.69	138
∑total				145.77		1.006	1078.6

$$K = \frac{1}{\sum \frac{1}{s_i}} = \frac{1}{145.77} = 0.0069$$

$$WQI = \frac{\sum(Q_i W_i)}{\sum W_i} = \frac{1078.6}{1.006} = 1072.2$$

Appendix C: water quality index table for 2nd unguwar bai sample.

parameter	v _i	v _o	s _i	$\frac{1}{s_i}$	$Q_i = 100 \left(\frac{v_i - v_o}{s_i - v_o} \right)$	$W_i = \frac{k}{s_i}$	Q _i W _i
pH	7.42	7	8.5	0.12	28	0.00082	0.02
Turbidity	0	0	5	0.2	0	0.0014	0
E.C	2060	0	1000	0.001	206	0.0000069	0.0014
DO	6.40	14.6	5	0.2	85.4	0.0014	0.12
TDS	1379	0	500	0.002	275.8	0.000014	0.0039
TSS	0	0	3	0.33	0	0.0023	0
Chloride	300	0	250	0.004	120	0.000028	0.0034
Calcium	60.9	0	300	0.0033	20.3	0.000023	0.00047
T. hardness	563	0	150	0.0067	375.3	0.000046	0.017
Iron	0.07	0	0.3	3.33	23.3	0.023	0.54
Copper	1.20	0	2	0.5	60	0.0035	0.21
Nitrate	63	0	10	0.1	630	0.00069	4.35
Zinc	2.55	0	1	1	255	0.0069	1.76
Manganese	5.4	0	0.05	20	10800	0.138	1490.4
Chromium	0.13	0	0.05	20	260	0.138	35.88
Lead	0.05	0	0.01	100		0.69	345

					500		
∑total				145.77		1.006	1878.31

$$K = \frac{1}{\sum \frac{1}{S_i}} = \frac{1}{145.77} = 0.0069$$

$$WQI = \frac{\sum(Q_i W_i)}{\sum W_i} = \frac{1878.31}{1.006} = \underline{1867.1}$$